

Information Service Engineering

Lecture 7: Knowledge Graphs - 2



Karlsruher Institut für Technologie



FIZ Karlsruhe

Leibniz Institute for Information Infrastructure

Prof. Dr. Harald Sack

FIZ Karlsruhe - Leibniz Institute for Information Infrastructure

AIFB - Karlsruhe Institute of Technology

Summer Semester 2021

3.1 Knowledge Representations and Ontologies

3.2 Semantic Web and the Web of Data

3.3 Linked Data Principles

3.4 How to identify and Access Things

3.5 Resource Description Framework (RDF) as simple Data Model

3.6 Creating new Models with RDFS

3.7 Knowledge Graphs

3.8 Querying Knowledge Graphs with SPARQL

3.9 More Expressivity with Web Ontology Language (OWL)

3.10 Knowledge Graph Programming

- ontologies & Semantic web
- Semantic web Technology Stack
- Linked Data Principles
- URIs and URLs
- Designator and Designatum
- HTTP Content Negotiation

The Semantic Web Technology Stack (not a piece of cake...)

Fully-Fledged
Semantic Web

Most apps use only a subset of the stack

Querying allows fine-grained data access


Standardized information exchange is key



Formats are necessary, but not too important

The Semantic Web is based on the Web

Linked Data uses a small
selection of technologies

LINKED DATA





3.1 Knowledge Representations and Ontologies

3.2 Semantic Web and the Web of Data

3.3 Linked Data Principles

3.4 How to identify and Access Things

3.5 Resource Description Framework (RDF) as simple Data Model

3.6 Creating new Models with RDFS

3.7 Knowledge Graphs

3.8 Querying Knowledge Graphs with SPARQL

3.9 More Expressivity with Web Ontology Language (OWL)

3.10 Knowledge Graph Programming

The Semantic Web Technology Stack (not a piece of cake...)

Most apps use only a subset of the stack

Querying allows fine-grained data access


Standardized information exchange is key

Formats are necessary, but not too important

The Semantic Web is based on the Web

Linked Data uses a small selection of technologies


LINKED DATA




Resource
Description
Framework

How to represent Knowledge?

- How do I represent the following fact:
“The Greenhouse Effect has been discovered in 1824” in an intuitive way?



Intuitive knowledge representation via a **directed graph**.



Resource Description Framework





Resource Description Framework

- **RDF Statements (RDF-Triple):**

Subject
URI

In RDF the predicate of a statement is referred to as "Property"

Property
URI


Object / Value
URI / Literal

N-Triples Serialization


```
<http://dbpedia.org/resource/Greenhouse\_effect> <http://dbpedia.org/ontology/discovered> "1824" .
```




Graph Representation



Resource Description Framework





Resource Description Framework

```

<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer> <http://dbpedia.org/resource/Joseph_Fourier> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Climate_change> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Atmosphere> .
...
<http://dbpedia.org/resource/Joseph_Fourier> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://dbpedia.org/ontology/Person> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthDate> "1768-03-21" .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthPlace> <http://dbpedia.org/resource/Auxerre> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/field> <http://dbpedia.org/resource/Physicist> .
...
<http://dbpedia.org/resource/Auxerre> <http://dbpedia.org/ontology/country> <http://dbpedia.org/resource/France> .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#lat> "47.798599"^^xsd:float .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#long> "3.567200"^^xsd:float .
...


```

Subject

Property

Object

RDF Triples



Resource Description Framework

```

<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer> <http://dbpedia.org/resource/Joseph_Fourier> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Climate_change> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Atmosphere> .
...
...
...

<http://dbpedia.org/resource/Joseph_Fourier> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://dbpedia.org/ontology/Person> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthDate> "1768-03-21" .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthPlace> <http://dbpedia.org/resource/Auxerre> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/field> <http://dbpedia.org/resource/Physicist> .
...
...
...

<http://dbpedia.org/resource/Auxerre> <http://dbpedia.org/ontology/country> <http://dbpedia.org/resource/France> .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#lat> "47.798599"^^xsd:float .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#long> "3.567200"^^xsd:float .
...
...
...

```

Individuals (Entities)



Resource Description Framework

<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
 <http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer> <http://dbpedia.org/resource/Joseph_Fourier> .
 <http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Climate_change> .
 <http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <<http://dbpedia.org/category/Atmosphere>> .

... ..

<http://dbpedia.org/resource/Joseph_Fourier> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <<http://dbpedia.org/ontology/Person>> .
 <http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthDate> "1768-03-21" .
 <http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthPlace> <http://dbpedia.org/resource/Auxerre> .
 <http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/field> <http://dbpedia.org/resource/Physicist> .

... ..

<http://dbpedia.org/resource/Auxerre> <http://dbpedia.org/ontology/country> <http://dbpedia.org/resource/France> .
 <http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#lat> "47.798599"^^xsd:float .
 <http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#long> "3.567200"^^xsd:float .

... ..

Classes / Concepts



Resource Description Framework

```


<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer> <http://dbpedia.org/resource/Joseph_Fourier> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Climate_change> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Atmosphere> .
...
...
...

<http://dbpedia.org/resource/Joseph_Fourier> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://dbpedia.org/ontology/Person> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthDate> "1768-03-21" .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthPlace> <http://dbpedia.org/resource/Auxerre> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/field> <http://dbpedia.org/resource/Physicist> .
...
...
...

<http://dbpedia.org/resource/Auxerre> <http://dbpedia.org/ontology/country> <http://dbpedia.org/resource/France> .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#lat> "47.798599"^^xsd:float .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#long> "3.567200"^^xsd:float .
...
...
...

```

Literals




Resource Description Framework

<http://dbpedia.org/resource/Greenhouse_effect> <**http://dbpedia.org/ontology/discovered**> "1824" .
 <http://dbpedia.org/resource/Greenhouse_effect> <**http://dbpedia.org/ontology/discoverer**> <http://dbpedia.org/resource/Joseph_Fourier> .
 <http://dbpedia.org/resource/Greenhouse_effect> <**http://purl.org/dc/terms/subject**> <http://dbpedia.org/category/Climate_change> .
 <http://dbpedia.org/resource/Greenhouse_effect> <**http://purl.org/dc/terms/subject**> <http://dbpedia.org/category/Atmosphere> .
 ...

<http://dbpedia.org/resource/Joseph_Fourier> <**http://www.w3.org/1999/02/22-rdf-syntax-ns#type**> <http://dbpedia.org/ontology/Person> .
 <http://dbpedia.org/resource/Joseph_Fourier> <**http://dbpedia.org/ontology/birthDate**> "1768-03-21" .
 <http://dbpedia.org/resource/Joseph_Fourier> <**http://dbpedia.org/ontology/birthPlace**> <http://dbpedia.org/resource/Auxerre> .
 <http://dbpedia.org/resource/Joseph_Fourier> <**http://dbpedia.org/ontology/field**> <http://dbpedia.org/resource/Physicist> .
 ...

<http://dbpedia.org/resource/Auxerre> <**http://dbpedia.org/ontology/country**> <http://dbpedia.org/resource/France> .
 <http://dbpedia.org/resource/Auxerre> <**http://www.w3.org/2003/01/geo/wgs84_pos#lat**> "47.798599"^^xsd:float .
 <http://dbpedia.org/resource/Auxerre> <**http://www.w3.org/2003/01/geo/wgs84_pos#long**> "3.567200"^^xsd:float .
 ...

Properties



Resource Description Framework

```


<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer> <http://dbpedia.org/resource/Joseph_Fourier> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Climate_change> .
<http://dbpedia.org/resource/Greenhouse_effect> <http://purl.org/dc/terms/subject> <http://dbpedia.org/category/Atmosphere> .
...
...
...

<http://dbpedia.org/resource/Joseph_Fourier> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://dbpedia.org/ontology/Person> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthDate> "1768-03-21" .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/birthPlace> <http://dbpedia.org/resource/Auxerre> .
<http://dbpedia.org/resource/Joseph_Fourier> <http://dbpedia.org/ontology/field> <http://dbpedia.org/resource/Physicist> .
...
...
...

<http://dbpedia.org/resource/Auxerre> <http://dbpedia.org/ontology/country> <http://dbpedia.org/resource/France> .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#lat> "47.798599"^^xsd:float .
<http://dbpedia.org/resource/Auxerre> <http://www.w3.org/2003/01/geo/wgs84_pos#long> "3.567200"^^xsd:float .
...
...
...


```

Vocabularies / Ontologies



Resource Description Framework

- **URIs and Literals**
 - **URIs** identify and reference resources uniquely.
 - **Literals** describe data values that don't have a separate existence.






RDF Literals and Data Types

- Typed literals can be expressed via **XML Schema datatypes**.
- Namespace for typed literals:
`http://www.w3.org/2001/XMLSchema#`
- Examples:
`"Semantics"^^<http://www.w3.org/2001/XMLSchema#string>`
`"1161.00"^^<http://www.w3.org/2001/XMLSchema#float>`
`"2015-08-02"^^<http://www.w3.org/2001/XMLSchema#date>`
- **Language Tags** denote the (natural) language of the text.
 - Example:
`"Semantik"@de , "Semantics"@en`


<http://www.w3.org/TR/2013/WD-rdf11-concepts-20130115/#xsd-datatypes>

Core types	xsd:string	Character strings
	xsd:boolean	true, false
	xsd:decimal	Arbitrary-precision decimal
IEEE floating-point numbers	xsd:integer	Arbitrary-size integer numbers
	xsd:double	64-bit floating point numbers
	xsd:float	32-bit floating point numbers
Time and date	xsd:date	Dates (yyyy-mm-dd) with or without time zone
	xsd:time	Times (hh:mm:ss.sss...) with or without time zone
	xsd:dateTime	Date and time with or without time zone
Recurring and partial dates	xsd:dateTimeStamp	Date and time with required time zone
	xsd:gYear	Gregorian calendar year
	xsd:gMonth	Gregorian calendar month
	xsd:gDay	Gregorian calendar day of the month
	xsd:gYearMonth	Gregorian calendar year and month
	xsd:gMonthDay	Gregorian calendar month and day
	xsd:duration	Duration of time
	xsd:yearMonthDuration	Duration of time (months and years)
	xsd:dayTimeDuration	Duration of time (days, hours, minutes, seconds)
	Limited-range integer numbers	xsd:byte
xsd:short		-32768...+32767 (16 bit)
xsd:int		-2147483648...+2147483647 (32 bit)
xsd:long		-9223372036854775808...+9223372036854775807 (64 bit)
xsd:unsignedByte		0...255 (8 bit)
xsd:unsignedShort		0...65535 (16 bit)
xsd:unsignedInt		0...4294967295 (32 bit)
xsd:unsignedLong		0...18446744073709551615 (64 bit)
xsd:positiveInteger		Integer numbers >0
xsd:nonNegativeInteger		Integer numbers ≥0
Encoded binary data	xsd:negativeInteger	Integer numbers <0
	xsd:nonPositiveInteger	Integer numbers ≤0
	xsd:hexBinary	Hex-encoded binary data
Miscellaneous XSD types	xsd:base64Binary	Base64-encoded binary data
	xsd:anyURI	Absolute or relative URIs and IRI references
	xsd:language	Language tags per [BCP47]
	xsd:normalizedString	Whitespace-normalized strings
	xsd:token	Tokenized strings
xsd:NMTOKEN	XML NMTOKENs	
xsd:Name	XML Names	
xsd:NCName	XML NCNames	



RDF Blank Nodes


- **Blank Nodes**
 - Denote the **existence of an individual** with specific attributes, but **without providing an identification or reference**.






RDF Serializations


- RDF comes with several different **serialization formats**:
 - N-Triples, RDF/XML, JSON, Turtle, TriG, N-Quads, RDFa, ...






RDF Serializations

- RDF comes with several different **serialization formats**:
 - N-Triples, RDF/XML, JSON, Turtle, TriG, N-Quads, RDFa, ...






RDF Serializations




- **N-Triples Notation**

- **URIs/IRIs** in angle brackets
- **Literals** in quotation marks
- Triple ends with a **period**

```
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer>
<http://dbpedia.org/resource/Joseph_Fourier> .
```



RDF Serializations



- **Turtle (Terse RDF Triple Language) Notation**

- Extension of N-Triples

```


@prefix dbo: <http://dbpedia.org/ontology/> .
@base <http://dbpedia.org/resource/> .

<Greenhouse_effect> dbo:discovered "1824" .
<Greenhouse_effect> dbo:discoverer <Joseph_Fourier> .
  
```

RDF/Turtle allows shortcuts and abbreviations for readability



RDF/Turtle




- Starting with N-Triples

```
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discovered> "1824" .
<http://dbpedia.org/resource/Greenhouse_effect> <http://dbpedia.org/ontology/discoverer>
<http://dbpedia.org/resource/Joseph_Fourier> .
```


```
@prefix dbo: <http://dbpedia.org/ontology/> .
@base <http://dbpedia.org/resource/> .
<Greenhouse_effect> dbo:discovered "1824" .
<Greenhouse_effect> dbo:discoverer <Joseph_Fourier> .
```

@prefix directive associates prefix-label with URI

@base directive provides URI to complement all relative URIs



RDF/Turtle



- Abbreviating RDF Triples in Turtle

```


@prefix dbo: <http://dbpedia.org/ontology/> .
@base <http://dbpedia.org/resource/> .

<Greenhouse_effect> dbo:discovered "1824" ;
                    dbo:discoverer <Joseph_Fourier> .
  
```

Semicolon indicates that subsequent triples have the same subject
(predicate list)



RDF/Turtle



- Abbreviating RDF Triples in Turtle

```


@prefix dct: <http://purl.org/dc/terms/> .
@prefix dbc: <http://dbpedia.org/category/> .
@base      <http://dbpedia.org/resource/> .

<Greenhouse_effect> dct:subject dbc:Atmosphere ,
                        dbc:Climate_change ,
                        dbc:Atmospheric_radiation .
  
```

Comma indicates that subsequent triples have same subject and property (object list)



RDF/Turtle



- Typed Literals

```

@prefix dbo: <http://dbpedia.org/ontology/> .
@prefix xsd: <http://www.w3c.org/2001/XMLSchema#> .
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@base <http://dbpedia.org/resource/> .

<Carbon_Dioxide> dbo:sublimationTemperature "-78.5"^^xsd:double ;
                  dbo:molarMass "44.009"^^xsd:double ;
                  dbo:discovered "1640-00-00"^^xsd:date ;
                  rdfs:label "Carbon Dioxide"@en .
  
```



RDF/Turtle




- **Multi Valued Relations**

- *CO₂ was discovered / rediscovered by two scientists at different times.*
- How to model this in RDF?
- **Problem:** unique association




RDF/Turtle




- **Multi Valued Relations**

- **Blank Nodes (Bnodes)** can be introduced to represent multi-valued relationships.
- Blank Nodes can be introduced for resources that don't need a name (auxiliary nodes).




RDF/Turtle




```
@prefix dbo: <http://dbpedia.org/ontology/> .  
@prefix xsd: <http://www.w3c.org/2001/XMLSchema#> .  
@base <http://dbpedia.org/resource/> .
```

```
[ ] dbo:discoverer <Jan_Baptist_van_Helmont> ;  
    dbo:discovered "1640-00-00"^^xsd:date .
```

anonymous blank node as subject




RDF/Turtle




```
@prefix dbo: <http://dbpedia.org/ontology/> .
@prefix xsd: <http://www.w3c.org/2001/XMLSchema#> .
@base <http://dbpedia.org/resource/> .
```

```
<Carbon_Dioxide> dbo:discovery [
  dbo:discoverer <Jean_Baptist_van_Helmont> ;
  dbo:discovered "1640-00-00"^^xsd:date
] ,
[
  dbo:discoverer <Joseph_Black> ;
  dbo:discovered "1750-00-00"^^xsd:date
] .
```

nested
anonymous blank
nodes



RDF/Turtle




```
@prefix dbo: <http://dbpedia.org/ontology/> .
@prefix xsd: <http://www.w3c.org/2001/XMLSchema#> .
@base <http://dbpedia.org/resource/> .
```

```
<Carbon_Dioxide> dbo:discovery _:ID1, _:ID2 .

_:ID1 dbo:discoverer <Jan_Baptise_van_Helmont> ;
      dbo:discovered "1640-00-00"^^xsd:date .

_:ID2 dbo:discoverer <John_Black> ;
      dbo:discovered "1750-00-00"^^xsd:date .
```

dereferenceable blank nodes
can only be referenced from
inside a document / graph



More RDF Datastructures



- **RDF Containers and RDF Collections**
 - Data structures to enumerate any resources or literals
 - Open lists (RDF Containers) and closed lists (RDF Collections)
 - No new semantics, just “syntactic sugar”
- **RDF Reification**
 - Abstraction for making “statements about RDF triples”
 - Useful for modeling data provenance
 - e.g. to model
“DBpedia states that Carbon Dioxide has been discovered in 1824.”

Further information:

E. Prud'hommeaux, G. Carothers,
RDF 1.1 Turtle, Terse RDF Triple Language, W3C Recommendation 25 February 2014
<https://www.w3.org/TR/turtle/>


- 3.1 Knowledge Representations and Ontologies
- 3.2 Semantic Web and the Web of Data
- 3.3 Linked Data Principles
- 3.4 How to identify and Access Things
- 3.5 Resource Description Framework (RDF) as simple Data Model
- 3.6 Creating new Models with RDFS**
- 3.7 Knowledge Graphs
- 3.8 Querying Knowledge Graphs with SPARQL
- 3.9 More Expressivity with Web Ontology Language (OWL)
- 3.10 Knowledge Graph Programming

What does it really mean?



Where does the intended meaning really come from?

What does it really mean?



We need more semantic expressivity...

The Semantic Web Technology Stack (not a piece of cake...)

RDF Schema

Most apps use only a subset of the stack

Querying allows fine-grained data access


Standardized information exchange is key

Formats are necessary, but not too important

The Semantic Web is based on the Web

Linked Data uses a small selection of technologies

LINKED DATA





RDF Schema

- **RDF Schema**, officially called “**RDF Vocabulary Description Language**”
- RDF Schema allows:
 - Definition of **classes** via **rdfs:Class**
 - Class instantiation in RDF via **rdf:type**
 - Example:

```
:Greenhouse_gas    rdf:type rdfs:Class .  
:Carbon_dioxide    rdf:type :Greenhouse_gas .
```

Carbon_dioxide ∈ greenhouse_gas

```
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .  
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .  
@prefix : <http://example.org/Space#> .
```



RDF Schema

- Definition of **properties** via `rdf:Property`
- Definition of **property restrictions on domain and range** via `rdfs:domain` and `rdfs:range`
- Example

```

:Person      rdf:type      rdfs:Class .
:discoverer  rdf:type      rdf:Property .
:discoverer  rdfs:domain   :Thing .
:discoverer  rdfs:range    :Person .
  
```

discoverer \subseteq Thing \times Person



RDF Schema

- Everything in the RDF model is a **resource**.
 - `rdfs:Class` `rdf:type` `rdfs:Resource` .
 - `rdf:Property` `rdf:type` `rdfs:Resource` .
 - `rdfs:Literal` `rdf:type` `rdfs:Resource` .
 - `rdfs:XMLLiteral` `rdf:type` `rdfs:Resource` .
 - `rdfs:Datatype` `rdf:type` `rdfs:Resource` .




RDF Schema

- Definition of **hierarchical relationships**:
 - **Subclasses** and **superclasses** via `rdfs:subClassOf`
 - Example:

```
:Greenhouse_gas rdfs:subClassOf :Air_pollutant .
```

`greenhouse_gas ⊆ Air_pollutant`





RDF Schema

- Definition of **hierarchical relationships**:

- **Subclasses** and **superclasses** via `rdfs:subClassOf`

- Example:

```
:Greenhouse_gas rdfs:subClassOf :Air_pollutant .
```

- **Subproperties** and **superproperties** via `rdfs:subPropertyOf`

- Example:

```
:sublimationTemperature rdfs:subPropertyOf  
:temperature .
```



RDF Schema

- Some more properties:
 - **rdfs:seeAlso**
defines a relation of a resource to another, which explains it.
 - **rdfs:isDefinedBy**
subproperty of `rdfs:seeAlso`, defines the relation of a resource to its definition.
 - **rdfs:comment**
comment, usually as text.
 - **rdfs:label**
„readable“ name of a resource (contrary to ID).



RDFS Example

```

@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix owl: <http://www.w3.org/2002/07/owl#>
@prefix : <http://example.org/Climate#> .

```

```

:Greenhouse_gas      rdf:type          rdfs:Class ;
                    rdfs:subClassOf :Air_pollutant .
:Person              rdf:type          rdfs:Class .
:Scientist           rdfs:subClassOf  :Person .
:Physicist           rdfs:subClassOf  :Scientist .
:Chemist             rdfs:subClassOf  :Scientist .

```

Class Definitions

```

:discoverer          rdf:type          rdf:Property ;
                    rdfs:domain owl:Thing .
                    rdfs:range       :Person .

```

Property Definitions


```

:Carbon_dioxide      rdf:type          :Greenhouse_gas ;
                    :discoverer      :Jan_Baptist_van_Helmont ;
                    :discoverer      :Joseph_Black .
:Jan_Baptist_van_Helmont rdf:type      :Physicist .
:Joseph_Black        rdf:type          :Chemist ;
                    rdfs:label       "Joseph Black"@en ;
                    rdfs:comment     "co-discovered CO2" .

```

Instance Definitions

How much knowledge (semantics) is there?



RDF(S) Semantics

- In difference to other data definition languages RDF(S) is based on a **formal semantics**.
- Formal semantics enables RDF(S) to draw **valid** and **sound logical inferences**.
- Examples:
 - `dbr:Joseph_Fourier rdfs:type dbo:Physicist .`
 - `dbo:Physicist rdfs:subClassOf dbo:Scientist .`
 - `dbo:discoveredBy rdfs:subPropertyOf dbo:perceivedBy`

`dbr:Joseph_Fourier ∈ dbo:Physicist`
`dbo:Physicist ⊆ dbo:Scientist`
`dbo:discoveredBy ⊆ dbo:perceivedBy`

Model-theoretic Semantics

Which Conclusions can we deduce with RDF(S) Semantics




Which Conclusions can we deduce with RDF(S) Semantics




(1) Deduction of **new facts** from a **class hierarchy**.

$$\forall i, c_1, c_2: T(i, \text{rdf:type}, c_1) \wedge T(c_1, \text{rdfs:subClassOf}, c_2) \rightarrow T(i, \text{rdf:type}, c_2)$$

Which Conclusions can we deduce with RDF(S) Semantics




Which Conclusions can we deduce with RDF(S) Semantics



(2) Deduction of entity **class membership** from the **domain** of one of its properties

$$\begin{aligned}
 \forall i_1, i_2, c_1, c_2, p: & \quad T(i_1, p, i_2) \wedge \\
 & \quad T(p, \text{rdfs:domain}, c_1) \wedge T(p, \text{rdfs:range}, c_2) \\
 & \quad \rightarrow T(i_1, \text{rdf:type}, c_1) \wedge T(i_2, \text{rdf:type}, c_2)
 \end{aligned}$$


Which Conclusions can we deduce with RDF(S) Semantics




(3) Deduction of entity **class membership** from the **range** of one of its properties

$$\begin{aligned}
 \forall i_1, i_2, c_1, c_2, p: & \quad T(i_1, p, i_2) \wedge \\
 & \quad T(p, \text{rdfs:domain}, c_1) \wedge T(p, \text{rdfs:range}, c_2) \\
 & \quad \rightarrow T(i_1, \text{rdf:type}, c_1) \wedge T(i_2, \text{rdf:type}, c_2)
 \end{aligned}$$

Which Conclusions can we deduce with RDF(S) Semantics



Which Conclusions can we deduce with RDF(S) Semantics




(4) Deduction of **new facts** from **subproperty** relationships

$$\forall i_1, i_2, p_1, p_2: T(i_1, p_1, i_2) \wedge T(p_1, \text{rdfs:subPropertyOf}, p_2) \rightarrow T(i_1, p_2, i_2)$$

- 3.1 Knowledge Representations and Ontologies
- 3.2 Semantic Web and the Web of Data
- 3.3 Linked Data Principles
- 3.4 How to identify and Access Things
- 3.5 Resource Description Framework (RDF) as simple Data Model
- 3.6 Creating new Models with RDFS
- 3.7 Knowledge Graphs**
- 3.8 Querying Knowledge Graphs with SPARQL
- 3.9 More Expressivity with Web Ontology Language (OWL)
- 3.10 Knowledge Graph Programming

Are Knowledge Graphs Relevant in Practice?

Gartner Hype Cycle for Emerging Technologies, 2019



gartner.com/SmarterWithGartner


Plateau will be reached:

● less than 2 years
 ● 2 to 5 years
 ● 5 to 10 years
 ○ more than 10 years
 ● obsolete before plateau

As of August 2019

Source: Gartner (August 2018)
© 2018 Gartner, Inc. and/or its affiliates. All rights reserved.

Are Knowledge Graphs Relevant in Practice?



gartner.com/SmarterWithGartner

Plateau will be reached:


- less than 2 years
- 2 to 5 years
- 5 to 10 years
- ▲ more than 10 years
- ⊗ obsolete before plateau

As of July 2020


Source: Gartner
© 2020 Gartner, Inc. and/or its affiliates. All rights reserved. Gartner and Hype Cycle are registered trademarks of Gartner, Inc. and its affiliates in the U.S.

Knowledge Graphs - A Definition


- A **Graph** consisting of **concepts, classes, properties, relationships,** and **entity descriptions**
- Based on **formal knowledge representations** (RDF(S), OWL)
- Data can be **open** (e.g. DBpedia, WikiData), **private** (e.g. supply chain data), or **closed** (e.g. product models)
- Data can be **original, derived, or aggregated**
- We distinguish
 - **instance data** (ground truth),
 - **schema data** (vocabularies, ontologies)
 - **metadata** (e.g. provenance, versioning, licensing)
- **Taxonomies** are used to categorize entities
- **Links** exist between internal and external data
- Including **mappings** to data stored in other systems and databases
- **Fully compliant to FAIR Data principles** (*Findable, Accessible, Interoperable, Reusable*)




Knowledge Graphs - A Definition (continued)



- A Knowledge Graph is a data set that is:
 - **structured** (in the form of a specific data structure)
 - **normalised** (consisting of small units, such as vertices and edges)
 - **connected** (defined by the - possibly distant - connections between objects)
- Moreover, Knowledge Graphs are typically:
 - **explicit** (created purposefully with an intended meaning)
 - **declarative** (meaningful in itself, independent of a particular implementation or algorithm)
 - **annotated** (enriched with contextual information to record additional details and meta-data)
 - **non-hierarchical** (more than just a tree-structure)
 - **large** (millions rather than hundreds of elements)



The Web of Data - A Web of Knowledge Graphs



Linked Data

- Linked Open Data (LOD) denote publicly available (RDF) Data on the Web, identified via URI and accessible via HTTP. Linked data link to other data via URI.

The Web of Data


- 9,960 datasets
 - >149 billion facts
 - >800 million links
- (April 2017)*

Knowledge Graph — for General Knowledge

HyperLink Artifacts

HyperData

HyperText




Linked Data Principles

1. Use **URIs** as names for things.
2. Use **HTTP URIs**, so that people can **look up** those names.
3. When someone looks up a URI, provide **useful information**, using the **standards** (RDF, SPARQL).
4. Include **links to other URIs**, so that they can discover more things.

Advantages of Linked Open Data vs. APIs

- **Simple** and **generic API** for various heterogeneous data sources enables **simple reuse** and **data sharing** among applications.
- **RDF Data model** guarantees (simple) **extensibility**.
- **Transport via http**, standard Port 80, prevents firewall adaption.
- **Ontologies** enable **meaningful connections** between data sources.
- **Reasoning** over Linked Data enables to **generate new knowledge**, i.e. inference from implicit to explicit knowledge.



Ontologies to Bind Them...


- Ontologies that keep the Web of Data together

- **OWL**

`owl:sameAs` connects identical individuals

`owl:equivalentClass` connects equivalent classes


`dbr:Joseph_Fourier owl:sameAs wd:Q8772 .`



Ontologies to Bind Them...

● SKOS

- „Simple Knowledge Organization System“
- Based on RDF and RDFS
- Applied for definitions and mappings of vocabularies and ontologies
 - `skos:Concept` (=classes)
 - `skos:narrower`
 - `skos:broader`
 - `skos:related`
 - `skos:exactMatch`,
 - `skos:narrowMatch`,
 - `skos:broadMatch`,
 - `skos:relatedMatch`




Popular Publicly Available Knowledge Graphs



	DBpedia	YAGO	Wikidata	OpenCyc	NELL
Version	2016-04	YAGO3	2016-08-01	2016-09-05	08m.995
# instances	5,109,890	5,130,031	17,581,152	118,125	1,974,297
# axioms	397,831,457	1,435,808,056	1,633,309,138	2,413,894	3,402,971
avg. indegree	13.52	17.44	9.83	10.03	5.33
avg. outdegree	47.55	101.86	41.25	9.23	1.25
# classes	754	576,331	30,765	116,822	290
# relations	3,555	93,659	11,053	165	1,334
Releases	biyearly	> 1 year	live	> 1 year	1-2 days

Knowledge Bases Timeline



Popular (Proprietary) Knowledge Graphs

	Data model	Size of the graph	Development stage
Microsoft	The types of entities, relations, and attributes in the graph are defined in an ontology.	~2 billion primary entities, ~55 billion facts	Actively used in products
Google	Strongly typed entities, relations with domain and range inference	1 billion entities, 70 billion assertions	Actively used in products
Facebook	All of the attributes and relations are structured and strongly typed, and optionally indexed to enable efficient retrieval, search, and traversal.	~50 million primary entities, ~500 million assertions	Actively used in products
eBay	Entities and relation, well-structured and strongly typed	Expect around 100 million products, >1 billion triples	Early stages of development and deployment
IBM	Entities and relations with evidence information associated with them.	Various sizes. Proven on scales documents >100 million, relationships >5 billion, entities >100 million	Actively used in products and by clients

Noy et al,

[Industry-scale Knowledge Graphs: Lessons and Challenges](#) (2019)

- 3.1 Knowledge Representations and Ontologies
- 3.2 Semantic Web and the Web of Data
- 3.3 Linked Data Principles
- 3.4 How to identify and Access Things
- 3.5 Resource Description Framework (RDF) as simple Data Model
- 3.6 Creating new Models with RDFS
- 3.7 Knowledge Graphs
- 3.8 Querying Knowledge Graphs with SPARQL**
- 3.9 More Expressivity with Web Ontology Language (OWL)
- 3.10 Knowledge Graph Programming

3. Knowledge Graphs - 2

Bibliography

- E. Prud'hommeaux, G. Carothers,
RDF 1.1 Turtle, Terse RDF Triple Language, W3C Recommendation 25 February 2014.
<https://www.w3.org/TR/turtle/>
- S. Hitzler, S. Rudolph,
Foundations of Semantic Web Technologies, Chapman / Hall, 2009.
- M. Krötzsch, [Knowledge Graphs](#), TU Dresden, WS2018.
- *Interested in the Greenhouse effect?*
P. Lynch, [How Joseph Fourier discovered the greenhouse effect](#), Irish Times,
Mar 21, 2019.

3. Knowledge Graphs - 2

Syllabus Questions

- How does RDF represent information?
- What is the difference between entities and (typed) literals in the role of RDF objects?
- What can RDF blank nodes be used for?
- What is the difference between RDF blank nodes and regular RDF nodes?
- Why is RDF alone not sufficient for knowledge representation?
- What is RDFS used for?
- What are the limits of RDF?
- What is DBpedia?
- What is a Wikipedia Infobox?
- What is a Knowledge Graph?
- Explain the Linked Data Principles.
- What are the advantages of Linked Data vs. proprietary APIs?
- What kind of links glue the Web of Data (Linked Data Cloud) together?
- Why are Knowledge Graphs fully compliant to the FAIR principles?